



Air-Cooled Scroll Chillers and Heat Pumps

Model CGA 040 to 115

Cooling capacity 14 - 40 kW

Model CXA 040 to 115

Cooling capacity 14 - 38 kW

Heating capacity 16 - 43 kW



Air-Cooled Scroll Chillers and Heat Pumps

Air/water chillers and heat pumps with axial fans and hermetic scroll compressors

Range description

- **CGA** chillers with/without hydraulic module
- **CGA-H** chillers with hydraulic module and built in water tank
- **CXA** heat pumps with/without hydraulic module
- **CXA-H** heat pumps with hydraulic module and built in water tank

Unit description

- Scroll compressor
- Fans propeller type
- Air side heat exchanger with seamless copper tubes and aluminium fins
- Water side heat exchanger steel brazed plate fitted with differential pressure switch and antifreeze protection electric heater
- Microprocessor-based controller to manage unit on/off mode, operating mode setting, parameters setting, and error code display
- Low ambient condensing pressure control with variable fan speed modulation
- Electrical panel with main switch
- Casing and panels in galvanised and painted steel



Options

- Low ambient temperature kit (down to -10°C)
- 3-way valve for domestic hot water (power supply and control included)
- Compressors sound jackets
- Soft - starter
- Control panel electric heater with thermostat
- Phase failure protection relay
- Epoxy coated condensing coils

Accessories

- Remote control panel
- Communication card RS485
- Flow switch
- Automatic water filling
- Water strainer
- Water gauges
- Rubber anti vibration mounts

Advantages

CXA units are designed in compliance with the new directive ErP 2009/125/EC relating to all products intended for heating and domestic hot water production.



DIGITAL DEFROST is a digital self-adaptive defrosting system able to intervene only in case of a consistent thickness formation of ice on the coils' fins. More specifically, the system reduces the number of defrosting cycles and activates the defrost function whenever necessary.



The DYNAMIC LOGIC CONTROL manages the differential of the inlet water temperature in accordance to the speed variation. Thanks to the DLC the number of the compressors' start decreases ensuring economic and energetic savings.



The function DYNAMIC SET POINT allows to change the set point simultaneously to always achieve the conditions of best comfort and, above all, the maximum energy saving.



Operating range		CGA	CXA cooling	CXA heating
Operating outdoor air temperature range (min./max.)	(°C)	5 (-10) / 43	5 / 43	-5 (-10) / 20
Leaving water temperature range (min./max.)	(°C)	-6 / 18	-6 / 18	26 / 55
Power supply	(V/Ph/Hz)	400/3+n/50		

* Temperatures within parentheses () can be achieved with low ambient temperature options.

Chiller Version

General data

CGA	Unit size	040	060	070	080	105	115
Cooling (1)							
Cooling capacity	kW	14.60	20.90	23.70	29.00	36.60	40.40
Total power input	kW	4.87	7.13	8.56	9.80	12.08	13.93
EER		3.00	2.93	2.77	2.96	3.03	2.90
ESEER		3.43	3.25	3.11	3.27	3.38	3.19
Efficiency class		B	B	C	B	B	B
Water flow	m ³ /h	2.50	3.58	4.07	4.98	6.28	6.94
Water pressure drop	kPa	48.30	32.90	42.00	19.00	30.30	36.60
Number of refrigerant circuits		1	1	1	1	1	1
Number of compressors		1	1	1	1	1	1
Compressor type		Scroll					
Sound pressure level (2)	dB(A)	53	49	50	53	51	58
Sound power level (3)	dB(A)	79	75	76	79	78	84
Hydraulic versions							
External head pressure	kPa	42	103	75	131	93	69
Volume of expansion vessels	l	1	1	1	1	1	1
Water tank volume	l	40	60	60	80	80	80

(1) Outdoor temperature 35°C - chilled water temperature in/out 12/7°C, in accordance with EN14511-3:2013.

(2) According to ISO 3744 at 5 m distance from the unit.

(3) According to ISO 9614 for Eurovent certified units, or ISO 3744 for non-certified units.

Dimensions and weights

CGA	Unit size	040	060	070	080	105	115
A	mm	1125	1465	1465	1671	1671	1671
B	mm	440	560	560	560	560	560
C	mm	1444	1448	1448	1687	1687	1687
Additional height - hydraulic version with water tank	mm	380	380	380	380	380	380
Shipping weight	kg	156	230	238	270	273	281
Additional shipping weight - hydraulic version	+ kg	7	11	11	12	12	12
Additional shipping weight - hydraulic version + water tank	+ kg	37	47	47	67	67	67



Heat Pump Version

General data

CXA	Unit size	040	060	070	080	105	115
Cooling (1)							
Cooling capacity	kW	13.80	19.80	22.50	27.50	34.80	38.40
Total power input	kW	4.84	7.12	8.56	9.79	12.08	13.96
EER		2.85	2.78	2.63	2.81	2.88	2.75
ESEER		3.26	3.09	2.95	3.11	3.22	3.03
EER Efficiency Class		C	C	D	C	C	C
Water flow	m ³ /h	2.37	3.40	3.86	4.73	5.97	6.59
Water pressure drop	kPa	43.50	29.60	37.80	17.10	27.30	32.90
Heating (2)							
Heating capacity	kW	15.80	22.10	25.50	29.80	38.20	43.10
Total power input	kW	5.18	7.29	8.39	9.90	12.61	14.13
COP		3.05	3.03	3.04	3.01	3.03	3.05
COP Efficiency Class		B	B	B	B	B	B
Heating (5)							
Rated, heating	kW	16.1	22.5	25.9	30.0	39.3	44.2
η_s	%	117	115	115	115	115	115
SCOP	kW/kW	3.01	2.96	2.95	2.95	2.96	2.96
Efficiency class		A	A	A	A	A	A
Water flow	m ³ /h	2.76	3.85	4.45	5.19	6.65	7.50
Water pressure drop	kPa	63.30	37.40	53.20	20.20	34.50	43.50
Number of refrigerant circuits		1	1	1	1	1	1
Number of compressors		1	1	1	1	1	1
Compressor type		Scroll					
Sound pressure level (3)	dB(A)	50	46	47	48	48	55
Sound power level (4)	dB(A)	76	72	73	74	75	81
Hydraulic versions							
External head pressure	kPa	48	113	88	138	103	83
Volume of expansion vessels	l	1	1	1	1	1	1
Water tank volume	l	40	60	60	80	80	80

(1) Outdoor temperature 35°C - chilled water temperature in/out 12/7°C, in accordance with EN14511-3:2013.

(2) Outdoor temperature 7°C 90% R.H. - hot water temperature in/out 40/45°C.

(3) According to ISO 3744 at 5 m distance from the unit.

(4) According to ISO 9614 for Eurovent certified units, or ISO 3744 for non-certified units.

(5) Ecodesign performance rating at low temperature conditions. Outdoor temperature: 7°C dry bulb/6°C wet bulb and hot water temperature in/out: 30°C/35°C.

Dimensions and weights

CXA	Unit size	040	060	070	080	105	115
A	mm	1125	1465	1465	1671	1671	1671
B	mm	440	560	560	560	560	560
C	mm	1444	1448	1448	1687	1687	1687
Additional height - hydraulic version with water tank	mm	380	380	380	380	380	380
Shipping weight	kg	174	252	260	304	307	315
Additional shipping weight - hydraulic version	+ kg	7	11	11	12	12	12
Additional shipping weight - hydraulic version + water tank	+ kg	37	47	47	67	67	67



Trane® is a brand of Ingersoll Rand®. Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Ingersoll Rand®, Trane®, Thermo King® and Club Car® — work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a global business committed to a world of sustainable progress and enduring results.



trane.com

ingersollrand.com